












Sumita Endoscope Lens

Objective lens units for 1/6 and 1/10 CCD/CMOS image sensors

All our lens units are equipped with aspheric lenses, which realizes brightness and deep depth-of-field.



1/6 Series

•			
Parameter	1/6 SEL140-032 1/6 SEL120-034		
Sensor Size	1/6inch		
Image Circle	3.0mm		
Cover Glass*1	0.3mm	0.5mm	


Object Distance (Design Value)	8mm	10mm
Depth of Field	3mm∼∞	5mm~100mm
Angle of view	140°	120°
F-number*2	3.5 to 8	3.5 to 10
Back focus*3	0.89mm	0.56mm
Distortion	<45%	<50%
TV distortion	>20%	>40%
Relative illumination	<16°	<1°


Outer diameter	φ3.2mm	φ3.4mm
Total length	4.35mm	5.4mm
Mount	-	-

IR cut filter	0	0
Sapphire cover glass	0	-

^{*1} It is not mounted on the standard lens unit.
*2 F-number is adjustable upon request.
*3 The thickness of cover glass is not included.

is	not	mounted	on	the	standard	lens	un









/ 1/10 Series

·			
Parameter	SEL120-022	SEL100-020	
Sensor Size	1/10inch		
Image Circle	1.8mm	1.8mm *4	
Cover Glass*1	0.5mm		

Object Distance (Design Value)	10mm	
Depth of Field	5mm~100mm	
Angle of view	120° 100°	
F-number*2	3.	5 to 10
Back focus* ³	0.93mm	
Distortion	<35% <25%	
TV distortion	>20%	>25%
Relative illumination	<10°	

Outer diameter	φ2.2mm	φ2mm
Total length	3.3	mm
Mount		-

IR cut filter	0
Sapphire cover glass	-

^{*1} It is not mounted on the standard lens unit.
*2 F-number is adjustable upon request.
*3 The thickness of cover glass is not included.
*4 Vignetting occurs in the corners.








Sumita Endoscope Lens

Objective lens units for 1/11 and 1/18 CCD/CMOS image sensors



/ 1/11 Series	日本日本 日本	
Parameter	1/11 SEL140-020	
Sensor Size	1/11inch	
Image Circle	1.49mm	
Cover Glass*1	0.15mm	

Object Distance (Design Value)	8mm	
Depth of Field	3mm~∞	
Angle of view	140°	
F-number*2	4 to 6	
Back focus* ³	0.38mm	
Distortion	<50%	
Relative illumination	>50%	
Chief ray angle	<33°	

Outer diameter	φ 2.0mm (Changeable)
Total length	1.77mm

IR cut filter	0
Sapphire cover glass	0

- *1 It is not mounted on the standard lens unit.
- *2 F-number is adjustable upon request. *3 The thickness of cover glass is not included.

φ1.5 ^{-0.005}	Image Sensor \$\phi 1.5^{-0.00}_{-0.01}\$ 0.37	Image Sensor 0.37 0.37	Image Senso 5-0.005 0.37	φ 1.5-0.015 0.7±0.05
/18 Series			7.1	

/ 1/10 361163	/	1/18	Series	
---------------	---	------	--------	--

Parameter	1/18 SEL080-015D	1/18 SEL100-015D	1/18 SEL120-015D	1/18 SEL100-015S
Sensor Size	1/18inch			
Image Circle	1.0mm			
Cover Glass*1	0.4mm			

Object Distance	8mm			
Depth of Field	3mm~100mm			
Angle of view	80°	100°	120°	100°
F-number*2	4.5/5/5.5/6			
Back focus*3	0.37mm			
Distortion	<20%	<32%	<46%	<24%
Relative illumination	>80%	>70%	>60%	>50%
Chief ray angle	<25°			

Outer diameter	φ1.5mm			
Total length	1.61mm	1.24mm	1.03mm	0.7mm

IR cut filter		-	
Sapphire cover	glass	-	

- *1 It is not mounted on the standard lens unit.
 *2 F-number is adjustable upon request.
 *3 The thickness of cover glass is not included.